

First round display in PowerView family line

Powerful high-speed processor for smooth animations

Bonded glare-free LCD screen for superior visibility in sunlight



FIRST ROUND DISPLAY IN THE POWERVERVIEW LINE-UP MERGES CLASSIC STYLE WITH MODERN PERFORMANCE

Introducing the PowerView® U35—the cornerstone of the all-new Ultimate Series. As the first round display in the acclaimed PowerView® lineup, the PowerView® U35 combines cutting-edge technology with a sleek, timeless design, redefining what a gauge can be. This revolutionary display is crafted for those who demand precision, durability, and aesthetic appeal in one seamless package.

Featuring an ultra-bright, high-resolution display, the PowerView® U35 ensures visibility in any environment, from intense sunlight to low-light conditions. With a lightning-fast processor, this display delivers real-time responsiveness, keeping you in control at all times. Engineered to handle the toughest conditions, its IP67 rating guarantees resilience

against dust, water, and extreme elements. The PowerView® U35 is more than a gauge replacement—it's the ultimate display solution for rugged applications, merging classic style with modern performance.

INTRODUCING THE POWERVERVIEW ULTIMATE SERIES

BUILT FOR POWERVERVIEW:

PowerVision Configuration Studio® software version 8.9+ lets programmers design stunning user interfaces, create intelligent applications with scripting and prototyping quickly with a vast library of standard engine parameters.

**IP
67**


ENOVATIONCONTROLS.COM/U35

POWerview® U35

78700696 01-2025

DIMENSIONS

IMAGES DO NOT REFLECT ACTUAL DISPLAY - FOR EXAMPLE ONLY



PRODUCT SPECIFICATIONS

COMPUTING		INTERFACES	
PROCESSOR	Dual-Core A7 Processor at 1.0 GHz	CAN	(1) CAN
OPERATING SYSTEM	QNX® Realtime Operating System	SERIAL	(1) USB 2.0
STORAGE	8GB Flash Memory	ETHERNET	(1) Ethernet
RAM	512 MB DDR3-SDRAM	ELECTRICAL/ENVIRONMENTAL	
MATERIAL & FINISH		OPERATING VOLTAGE	6 – 36 VDC, reverse polarity protected
BEZEL	Stainless Steel - Black Powder Coat	OPERATING TEMPERATURE	-22°F TO +158°F [-30°C TO +70°C]
COVER GLASS	Soda Lime Glass, AG Etch	STORAGE TEMPERATURE	-40°F TO +185°F [-40°C TO +85°C]
HOUSING	Plastic - Black	PROTECTION	IP67
DISPLAY/HMI		VIBRATION	Swept Sine (10-2000-10Hz) 10g Peak, 3 Axis Random (10-2000Hz) 8.17g RMS, 3 Axis
SCREEN	3.5-Inch Round, 24-bit color	SHOCK	±50G IN 3 Axis
RESOLUTION	640 x 516	EMC/EMI	(2024/30/EU)
CONTRAST RATIO / BRIGHTNESS	600:1 1000 cd/m ²	⚠ WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov .	
TOUCH PANEL	Projected capacitive (PCAP) with glove touch		
SURFACE	Anti-glare finish		
AMBIENT LIGHT SENSOR	Yes		

FOR MODEL & PART INFORMATION

FOR MANUAL & SUPPORT DOCUMENTS

FOR SUPPORT & WARRANTY

ENOVATIONCONTROLS.COM/U35

SUPPORT.ENOVATIONCONTROLS.COM

ENOVATIONCONTROLS.COM/SUPPORT

SALES CONTACT



CONTACT

✉ sales@novationcontrols.com

☎ +1 918.317.4100

www.novationcontrols.com

CORPORATE HEADQUARTERS

5311 S 122nd E Ave
Tulsa, Oklahoma, USA 74146

United States • United Kingdom • India • China



FM 28221 (Tulsa, OK-USA)
FM 29422 (UK)